

## Technical data

### Cassette Multi-Split indoor unit



| Model                               |                                    |               | FMA-12CRD/DVI        | FMA-18CRD/DVI        |
|-------------------------------------|------------------------------------|---------------|----------------------|----------------------|
| Power supply                        |                                    | V/Ph/Hz       | 220-240~/1/50        | 220-240~/1/50        |
| Cooling                             | Capacity                           | kW            | 3,51                 | 5,27                 |
|                                     | Power Input                        | W             | 37                   | 40                   |
|                                     | Rated Current                      | A             | 0,17                 | 0,18                 |
| Heating                             | Capacity                           | kW            | 3,95                 | 5,74                 |
|                                     | Power Input                        | W             | 37                   | 40                   |
|                                     | Rated Current                      | A             | 0,17                 | 0,18                 |
| Indoor sound pressure(S/H/M/L/Mute) |                                    | dB(A)         | 42/40/38/36/44/30/27 | 46/43/40/38/36/32/28 |
| Air Flow Volume                     |                                    | m3/h          | 650                  | 750                  |
| Connecting Pipe                     | Liquid                             | Inches        | 1/4"                 | 1/4"                 |
|                                     | Gas                                | Inches        | 3/8"                 | 3/8"                 |
|                                     | Maxium length for each indoor unit | m             | 25                   | 25                   |
|                                     | Maxium heigth difference           | m             | 15                   | 15                   |
|                                     | Standard weight charged            | m/indoor unit | 5                    | 5                    |
|                                     | Extra weight charge                | g/m           | 15                   | 15                   |
| Dimensions (WxHxD)                  | Indoor                             | mm            | 570x570x245          | 570x570x245          |
| Dimension of Package (WxHxD)        | Indoor                             | mm            | 718x657x301          | 718x657x301          |
| Weight Netto                        | Indoor                             | kg            | 2,7                  | 2,7                  |
| Weight Brutto                       | Indoor                             | kg            | 4,25                 | 4,25                 |
| Wi-fi*                              |                                    |               | +                    | +                    |

\*Remote control of the NØRDIS unit requires an additional integrated Wi-Fi module.

Specifications are subject to change without notice. For actual device specifications, see. See the stickers on the device.