

Techniniai duomenys

Orion Evo Multi Split vidinis įrenginys



Modelis			OE09TC1	OE12TC1	OE18TC1	OE24TC1
Įtampa		F/V/Hz	220-240~/1/50	220-240~/1/50	220-240~/1/50	220-240~/1/50
Nominali galia	Vėsinimas	kW	2,61(0,94-3,70)	3,52(1,00-4,60)	5,2 (1,25-5,9)	7,0 (1,8-7,8)
	Šildymas	kW	3,32(0,94-4,00)	3,86(1,00-4,90)	5,50(1,25-6,69)	7,10(1,85-7,96)
Wi-Fi		+/-	+	+	+	+
Vidinis įrenginys						
Matmenys (PxAxG)		mm	820×306×195	820×306×195	920×306×195	1100×333×222
Įpakavimo matmenys (PxAxG)		mm	890×380×265	890×380×265	990×380×265	1165×405×295
Svoris netto		kg	9	9	10	11
Svoris brutto		kg	11	11	13	17
Oro srautas		m3/h	680/650/610/570/540/500/460	680/650/610/570/540/500/460	900/810/760/700/650/590/530	1150/1070/1010/940/890/830/750
Garso slėgis 1 m. atstumu		db(A)	44/41/37/34/29/25/19	44/41/37/34/29/25/19	47/42/40/38/36/34/32	50/44/40/37/34/30/26
Garso galia		db(A)	54/50/47/44/39/35/29	54/50/47/44/39/35/29	57/52/50/48/46/44/42	60/54/50/47/44/40/36
Tarpblokinis kabelis		mm2	4x0,75	4x0,75	4x0,75	4x0,75
Vamzdžių diametro		col/mm	1/4"-3/8"/(Ø6,35-Ø9,52)	1/4"-3/8"/(Ø6,35-Ø9,52)	1/4"-1/2"/(Ø6,35-Ø12,70)	1/4"-1/2"/(Ø6,35-Ø12,70)