

Technical data

NØRDIS Ultima Mono Split type indoor unit with DHW Tank



Indoor Unit Model with DHW				HLT-9-250-3S			HLT-12-250-3S
Compatible Outdoor Units				HLT6MONO-S	HLT9MONO-S	HLT12MONO-S	HLT16MONO-3S
Power Supply			V/Hz/Ph	380-415/50/3			
Circuit Breaker			A	16			
Power Cable			mm2	5x2,5			
Backup Heater			kW	9 (3+6)			
3-way Diverting Valve				LK Systems			
DHW tank		Volume	l	250			
		Material		Duplex 2205 SS			
Water Flow Meter				Vortex			
Circulation Pump (Head, m)				Grundfos (9)			Grundfos (12)
Water Side	Piping Connection		Inch	G1"			G1-1/4"
	Allowable Water Flow - Min./Rated/Max.		l/s	0,20/0,29/0,37	0,27/0,38/0,50	0,40/0,57/0,75	0,50/0,72/0,93
			l/min	12/17,4/22,2	16,2/22,8/30	24/34,2/45	30/43,2/55,8
			m3/h	0,72/1,04/1,33	0,97/1,37/1,8	1,44/2,05/2,7	1,8/2,59/3,35
Dimensions	Net Dimensions (L x D x H)		mm	600x710x1720			
	Net Weight		kg	115			