

Technical Data

Console Multi Split Indoor Unit



Model			FMA-09CON/DVI	FMA-12CON/DVI	FMA-18CON/DVI
Power supply		V/Ph/Hz	220-240~/1/50	220-240~/1/50	220-240~/1/50
Cooling	Capacity	kW	2,63	3,51	5,27
	Power Input	W	35	37	48
	Rated Current	A	0,15	0,17	0,21
Heating	Capacity	kW	2,78	3,95	5,74
	Power Input	W	35	37	48
	Rated Current	A	0,15	0,17	0,21
Indoor sound pressure(S/H/M/L/Mute)		dB(A)	44/42/39/36/33/30/27	44/42/39/36/33/30/27	46/43/40/38/36/32/28
Air Flow Volume		m3/h	650	650	800
Connecting Pipe	Liquid	Inches	1/4"	1/4"	1/4"
	Gas	Inches	3/8"	3/8"	3/8"
	Maxium length for each indoor unit	m	25	25	25
	Maxium heigth difference	m	15	15	15
	Standard weight charged	m/indoor unit	5	5	5
	Extra weight charge	g/m	15	15	15
	Indoor	mm	700×600×215	700×600×215	700×600×215
Dimension of Package (WxHxD)	Indoor	mm	775×725×280	775×725×280	775×725×280
Weight Netto	Indoor	kg	14,5		
Weight Brutto (excluding wire control)	Indoor	kg	16,5		
Weight Brutto (excluding wire control)	Indoor	kg	18	18	21
Wi-fi*			+	+	+

*Remote control of the NØRDIS unit requires an additional integrated Wi-Fi module.

Specifications are subject to change without notice. For actual device specifications, see. See the stickers on the device.