

Technical Data

Ducted Multi Split Indoor Unit



Model			FMA-09DRD/DVI	FMA-12DRD/DVI	FMA-18DRD/DVI
Power supply		V/Ph/Hz	220-240~/1/50	220-240~/1/50	220-240~/1/50
Cooling	Capacity	kW	2,63	3,51	5,27
	Power Input	W	35	35	48
	Rated Current	A	0,16	0,16	0,21
Heating	Capacity	kW	2,78	3,95	5,74
	Power Input	W	35	35	48
	Rated Current	A	0,16	0,16	0,21
Indoor sound pressure (S/H/M/L/Mute)		dB(A)	43/41/39/37/34/30/27	43/41/39/37/34/30/27	46/43/40/38/36/32/28
Indoor sound power (S/H/M/L/Mute)		dB(A)	55/52/49/47/44/40/37	55/52/49/47/44/40/37	56/53/50/48/46/42/38
Air Flow Volume		m3/h	600	600	850
Connecting Pipe	Liquid	Inches	1/4"	1/4"	1/4"
	Gas	Inches	3/8"	3/8"	3/8"
	Maxium length for each indoor unit	m	25	25	25
	Maxium heigth difference	m	15	15	15
	Standard weight charged	m/indoor unit	5	5	5
	Extra weight charge	g/m	15	15	15
Dimensions (WxHxD)	Indoor	mm	700×490×200	700×490×200	920×490×200
Dimension of Package (WxHxD)	Indoor	mm	900×555×250	900×555×250	1120×555×250
Weight Netto	Indoor	kg	15	15	18
Weight Brutto (excluding wire control)	Indoor	kg	18	18	21
Wi-fi*			+	+	+

*Remote control of the NØRDIS unit requires an additional integrated Wi-Fi module.

Specifications are subject to change without notice. For actual device specifications, see. See the stickers on the device.