

**PRODUCT FICHE**

NØRDIS air-to-water heat pump



Energy labelling regulation: (EU)811/2013

Ecodesign regulation: (EU)813/2013

Technical parameters											
Model(s):		Outdoor unit: HLT230MONO3 / Indoor unit: HLT CONTROL BOX									
Air-to-water heat pump:		YES									
Water-to-water heat pump:		NO									
Brine-to-water heat pump:		NO									
Low-temperature heat pump:		NO									
Equipped with a supplementary heater:		NO									
Heat pump combination heater:		NO									
Declared climate condition:		AVERAGE									
Parameters are declared for medium-temperature application.											
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	$P_{rated}$	29.00	kW	Seasonal space heating energy efficiency	$\eta_s$	159	%	Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature $T_j$			
Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature $T_j$				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature $T_j$							
$T_j = -7\text{ °C}$	$P_{dh}$	25.82	kW	$T_j = -7\text{ °C}$	$COP_d$	2.23	-	$T_j = -7\text{ °C}$	$COP_d$	2.23	-
$T_j = +2\text{ °C}$	$P_{dh}$	15.57	kW	$T_j = +2\text{ °C}$	$COP_d$	4.05	-	$T_j = +2\text{ °C}$	$COP_d$	4.05	-
$T_j = +7\text{ °C}$	$P_{dh}$	10.66	kW	$T_j = +7\text{ °C}$	$COP_d$	5.40	-	$T_j = +7\text{ °C}$	$COP_d$	5.40	-
$T_j = +12\text{ °C}$	$P_{dh}$	10.04	kW	$T_j = +12\text{ °C}$	$COP_d$	7.63	-	$T_j = +12\text{ °C}$	$COP_d$	7.63	-
$T_j =$ bivalent temperature	$P_{dh}$	25.82	kW	$T_j =$ bivalent temperature	$COP_d$	2.23	-	$T_j =$ bivalent temperature	$COP_d$	2.23	-
$T_j =$ operation limit temperature	$P_{dh}$	22.36	kW	$T_j =$ operation limit temperature	$COP_d$	1.85	-	$T_j =$ operation limit temperature	$COP_d$	1.85	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$	$P_{dh}$	19.68	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$	$COP_d$	1.62	-	For air-to-water heat pumps: $T_j = -15\text{ °C}$	$COP_d$	1.62	-
Bivalent temperature	$T_{biv}$	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	$P_{cych}$	-	kW	Cycling interval efficiency	$COP_{cyc}$	-	-	Cycling interval efficiency	$COP_{cyc}$	-	-
Degradation co-efficient (**)	$C_{dh}$	0.90	-	Heating water operating limit temperature	WTOL	60	°C	Heating water operating limit temperature	WTOL	60	°C
Power consumption in modes other than active mode				Supplementary heater							
Off mode	$P_{OFF}$	0	kW	Rated heat output (*)		$P_{sup}$	6.6	kW			
Thermostat-off mode	$P_{TO}$	0.067	kW	Type of energy input		Electrical					
Standby mode	$P_{SB}$	0.069	kW								
Crankcase heater mode	$P_{CK}$	0.066	kW								
Other items											
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors		-	11000	m <sup>3</sup> /h			
Sound power level, indoors/ outdoors	$L_{WA}$	-/55	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger		-	-	m <sup>3</sup> /h			
Annual energy consumption	$Q_{HE}$	14923	kWh								
For heat pump combination heater:											
Declared load profile	-			Water heating energy efficiency		$\eta_{wh}$	-	%			
Daily electricity consumption	$Q_{elec}$	-	kWh	Daily fuel consumption		$Q_{fuel}$	-	kWh			
Annual electricity consumption	AEC	-	kWh	Annual fuel consumption		AFC	-	GJ			
Contact details	NØRDIS EUROPE SP. Z O.O. Opolska 38 55-011 Siechnice, Poland										
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output $P_{rated}$ is equal to the design load for heating $P_{designh}$ , and the rated heat output of a supplementary heater $P_{sup}$ is equal to the supplementary capacity for heating $sup(T_j)$ .											
(**) If $C_{dh}$ is not determined by measurement then the default degradation coefficient is $C_{dh} = 0,9$ .											