

Technical Data

One way Multi Split Indoor Unit



Model			FMA-09C1RD/DVI	FMA-12C1RD/DVI	FMA-18C1RD/DVI	FMA-24C1RD/DVI
Power supply		V/Ph/Hz	220-240~/1/50	220-240~/1/50	220-240~/1/50	220-240~/1/50
Cooling	Capacity	kW	2,64	3,52	5,28	7,03
	Power Input	W	40	40	50	60
	Rated Current	A	0,2	0,2	0,32	0,38
Heating	Capacity	kW	2,64 kW	3,52	5,28	7,03
	Power Input	W	40	40	50	60
	Rated Current	A	0,2	0,2	0,32	0,38
Indoor sound pressure(S/H/M/L/Mute)		dB(A)	46/42/39/37/35/32/30	46/42/39/37/35/32/30	49/46/42/39/35	52/50/46/41/35
Indoor sound power (S/H/M/L/Mute)		dB(A)	56/52/49/47/45/42/40	56/52/49/47/45/42/40	59/56/52/49/45	62/60/56/51/45
Air Flow Volume		m ³ /h	700	700	1150	1150
Connecting Pipe	Liquid	Inches	1/4"	1/4"	1/4"	1/4"
	Gas	Inches	3/8"	3/8"	1/2"	1/2"
	Maxium length for each indoor unit	m	25	25	25	25
	Maxium heigth difference	m	15	15	15	15
	Standard weight charged	m/indoor unit	5	5	5	5
	Extra weight charge	g/m	15	15	15	15
Net dimensions (W x H x D)	Indoor	mm (no panel)	900*450*130	900*450*130	1200*450*130	1200*450*130
Net weight	Indoor	kg	11	11	13	13
Packing dimensions(W x H x D)	Indoor	mm (no panel)	1182*535*237	1182*535*237	1470*240*535	1470*240*535
Gross weight	Indoor	kg	17	17	19,6	19,6
Net dimensions (W x H x D)	Panel	mm	1180*500*68	1180*500*68	1480*500*68	1480*500*68
Net weight	Panel	kg	5,5	5,5	6	6
Packing dimensions(W x H x D)	Panel	mm	1275*565*195	1275*565*195	1575*140*565	1575*140*565
Gross weight	Panel	kg	8,5	8,5	9	9

*Remote control of the NØRDIS unit requires an additional integrated Wi-Fi module.

Specifications are subject to change without notice. For actual device specifications, see. See the stickers on the device.