

Model			9K	12K
<b>Power Supply</b>		F/V/Hz	1F/~230V/50Hz	1F/~230V/50Hz
<b>Cooling</b>	Cooling, kW	kW	2.6 (0.94-3.30)	3.4 (1.00-3.77)
	Cooling Power Input (min-nom-max)	kW	0.24-0.80-1.38	0.29-1.13-1.5
	Cooling Current	A	4.6 (1.2~8.0)	5.8 (1.5~9.0)
	Rated Current	A	4.6	5.8
	ERR	W/W	3.25	3.01
	SEER	W/W	6.3	6.1
Energy Class			A++	A++
<b>Heating</b>	Capacity, kW	kW	2.61 (0.94-3.36)	3.42 (1.00-3.81)
	Heating Power Input (min-nom-max)	kW	0.24-0.69-1.55	0.29-0.92-1.72
	Heating Current	A	4.1 (1.2~9.0)	4.7 (1.5~10.0)
	Rated Current	A	4.1	4.7
	COP	W/W	3.73	3.71
	SCOP	W/W	4	4
Energy Class			A+	A+
Wi-Fi		+/-	+	+
<b>Indoor Unit</b>				
Dimension (WxHxD)		mm	698x255x190	777x250x205
Dimension of Package (LxWxH)		mm	764x325x257	850x320x275
Weight netto		kg	6.5	8.5
Weight brutto		kg	8.5	10.5
Air Flow Volume		m3/h	420	550
Sound Pressure Level		db(A)	40/37/33/25/22	40/37/33/25/22
<b>Outdoor unit</b>				
Dimension (WxHxD)		mm	715x492x240	715x492x240
Dimension of Package (LxWxH)		mm	818x325x520	818x325x520
Weight netto		kg	24	24
Weight brutto		kg	26	26
Air Flow Volume		m3/h	1900	1900
Sound Pressure Level		db(A)	50	50
Connection Pipe	Refrigerant Liquid Pipe/Refrigerant Gas Pipe	in/mm	1/4"-3/8"/ (Ø6.35-Ø9.52)	1/4"-3/8"/ (Ø6.35-Ø9.52)
	Refrigerant Charge	kg	0.53	0.55
	Additional Refrigerant	g/m	15	15
	Max. Distance Length	m	25	25
	Max. Elevation	m	10	10
Power Cable	Power Cable	mm2	3x1.0	3x1.5
	Automatic Switch	A	10	16
	Communication Cable	mm2	4x0.75	4x0.75
Cooling Operation Ambient Temperature Range		°C	-15~53	-15~53
Heating Operation Ambient Temperature Range		°C	-20~30	-20~30