

Indoor unit model name Outdoor unit model name

Refrigerante R32

Altair Plus NDI-A24TC1 Altair Plus NDO-A24TC1

675

54	dB(A)
67	dB(A)
	• .

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself

and always ask a professional.

Cooling mode 6.1 SEER A** Energy efficiency class

6.8 kW Design load (Pdesignc) Energy consumption, 390 kWh per year, based on standard test results.

GWP

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Average)

SCOP 4.0 Energy efficiency class A٠ 4.8 kW (-10°C) Design load (Pdesignh) (-10°C) 4.5 kW Declared capacity

Back up heating capacity 0.3 kW (-10°C) Energy consumption, 1680 kWh per year.based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Warmer) Optional

SCOP 5.1 Energy efficiency class Α*** 5.8 kW

Design load (Pdesignh) (2°C) Declared capacity 5.8 kW 0.0 kW (2°C) Back up heating capacity

Energy consumption. 1592 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(2°C)

Heating mode (Colder) Optional

SCOP 3.4 Energy efficiency class Α

4.7 kW (-22°C) Design load (Pdesignh) (-22°C) 4.4 kW Declared capacity

0.3 kW Back up heating capacity (-22°C) 2903 kWh per year. based on standard test results. Energy consumption,

Actual energy consumption will depend on how the appliance is used and where it is located.